

## Medical ReVitalization, Inc CoolSpot II



## Features

- The aesthetically appealing CoolSpot II offers incredibly pure, white light along with a guaranteed no-drift arm, high-intensity setting and variable spot size control. The CoolSpot II offers intensity of up to 60,000 lux (5574 fc) at 1 meter. The CoolSpot II examination light is the spotlight of choice

## **Specifications**

- Up to 60,000 lux (5574 fc) at 1 meter
- 4300 K color temperature
- CRI (Color Rendering Index) of 94
- Bi-level dimmer for variable intensity
- Variable spot size of 2'' 10'' (5 cm 25 cm)
- New, improved and easy to clean housing design with convenient SteriHandle for positioning
- Removable, autoclavable center SteriHandle design allows removal or replacement of SteriHandle with one hand (for ensuring sterile

procedures)

- 150-watt halogen bulb provides 600-hour average bulb life on standard setting
- Friction knob allows user to adjust friction on the self-balancing arm positioning to desired tension without a tool
- Mounting systems meet California Seismic
  Codes
- Assembled in USA
- 120V standard models: CS316FL, CS316SC, CS316DC, CS316W,CS316ST,CS316DT
- 100V standard models: CS315FL, CS315SC, CS315DC, CS315W,CS315ST,CS315DT
- 230/240V standard models: CS325FL, CS325SC, CS325DC, CS325W, CS325ST, CS325DT