



MEDICAL REVITALIZATION, INC

Stryker Prime 1105,1107,1115,1125



Features

- Thermoformed ABS base with extra capacity storage tray
- 700 lb weight capacity
- 26-inch wide patient surface with 3-inch Enhanced Comfort Mattress
- Less than 21-inch low height
- Integrated utility tray
- Litter-mounted oxygen bottle holder
- Power-washable design (1105 and 1115 only)
- Four-wheel, center-locking brake system with dual end activators
- Dual side-mounted foot control hydraulics with uni-lower pedal

Specifications

- Maximum Height: 34", Minimum Height: 20"
- Width: Siderails Down 30.25", Siderails Up 34"
- Weight Capacity: 700lbs
- Length: 85"
- Sideralls: $\pm 45^\circ$
- Litter Positioning: Backrest 0° - 90° , Knee Gatch: 0° - 40° , Trend: $\pm 17^\circ$
- Maximum Angle 87.5°
- Patient Surface: 26" x 75.25"
- Caster Diameter: 8"

- Glideaway Siderails with integrated foot end push/pull handles
- 4 integrated IV receptacles
- +/- Trendelenburg
- 8-inch Omni Surface Casters with integrated wheel covers
- Pneumatic backrest/stationary foot
- Constant descent hydraulics
- Dual end brake/steer controls

Model

- 1105: Fifth Wheel
- 1115: Big Wheel
- 1125: Zoom Drive, Low Height: 23"

Refurbishment Process

- Disassemble Bed
- Steam clean frame and components
- Paint frame
- Install new brake mechanisms on both sides
- Sand and repaint shrouds with our special 2 part polyurethane coating
- Rebuild pumps with new seals and adjust pumps speed and travel
- New stickers per customers choice of color
- Clean, adjust and lube brake/steer components
- New bumpers and plastic
- 1 year warranty